

professional welding supplies



ASPECT® 200

Leading technology in TIG AC/DC welding with a user friendly interface and innovative remote control system from the torch

SINGLE PHASE AC/DC TIG WELDER

The Aspect® 200 welder has TIG AC & DC functions (four wave shapes, pulse, adjustable balance and offset) making it ideal for critical AC or DC TIG welding applications. It offers a simple control panel with bright digital display and an innovative control system from the torch. It can be simply changed to a water cooled unit by adding the COOL ARC® 24 water cooler.





Stick, TIG Pulse, TIG HF, LIFT TIG

CC







Why ASPECT® 200?

» Superb arc performance

Excellent HF ignition, stable & fast arc, minimum current 2A

» Advanced TIG AC & DC Functions

Four wave shapes, pulse, adjustable balance and offset, innovative and simple control panel, AC auto setting

Generator compatible ideal for site use

» Cellulosic capability

» Bright digital display

easy set up buttons, 9 memories, new control from the TIG torch

» Energy efficient

1 phase buck-boost circuit for energy saving

» Robust design

Potted PCB's, True HD design (special protection for use in harsh conditions)

» Best aluminium welding performance

SPECIFICATIONS

Item	Primary Voltage	Current	Rated	Fuse Size	Effective consumption (A)	0.C.V	Weight	Dimensions	Protection
Number	(50-60Hz)	Range (A)	Output	(A) (slow)		(V DC)	(kg)	WxLxD (mm)	Class
K14189-1	115/230V/1Ph +/- 15%	2-200	200A@35% 130A@100%	16A	16	107	23	419 x 246 x 506	IP23

FRONT CONTROLS



- 1 Volts and Amps display / Parameters / Alarms
- 2 Input Voltage / Overheating / Remote Control / LED VRD
- 3 Polarity / Process / Trigger Mode / AC Mode
- Memory Display / Push Buttons to store and recall programs (9 memories)
- **6** Encoder to set values
- 6 TIG sequencer / Pulsed TIG / Advanced Menus

TO ORDER

Designation	Item Number		
ASPECT® 200	K14189-1		
KIT 35C50	W000011139		
PROTIG NGS 30 EB C5B-S - 200A@35% - 5m	W000278398-2		
PROTIG NGS 30 EB C5B-S - 200A@35% - 8m	W000278399-2		
PROTIG NGS 10W EB C5B-S - 220A@100% - 5m	W000278402-2		
PROTIG NGS 10W EB C5B-S - 220A@100% - 8m	W000278403-2		
Foot Amptrol	K870		
Remote control (15 m)	K14147-1		
Extension Remote control (15 m)	K14148-1		
Cool Arc 24	K14190-1		
Coolant FREEZCOOL	W000010167		
Cart 24	K14191-1		







Storage compartment for small sparts and

COOL ARC 24



- Filling level indicator
- Light and modular design
- Powerful pump
- Low noise

FREEZCOOL

Specially designed for the cooling of welding torches.



- High electrical resistivity
 Anti-freezing protection down to -27 °C
- Anti-corrosion and anti-algae growth

SELECTION

