

Printing date 22/10/2021

Reviewed on 29/10/2021

Safety Data Sheet

1 IDENTIFICATION

Product identifier

Trade name: Promax Silver Brazing 55N Flux Powder 200g

Other means of identification:

SKU # 204170

Recommended use and restriction on use

Recommended use: All Purpose Brazing Flux Powder is a general purpose brazing flux. Use with low fuming bronze and nickel silver brazing alloys steel, cast iron and copper-based alloys.

Restrictions on use: Exclusively used in torch brazing.

Manufacturer/Importer/Supplier/Distributor information

Importer:

NEW ZEALAND
Proline Welding Supplies
9 Kidson Place
Stoke
Nelson 7011
0800 699 353

Safety Data Sheet Questions: sales@prolinewelding.com

Website: www.prolineindustrial.co.nz

New Zealand National Poisons Centre/Helpline (24 hours) 0800 POISON (0800 764 766)
Fire Service - Ambulance – 111

2 HAZARD(S) IDENTIFICATION

GHS classification of the substance/mixture.

Classified according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classification of the substance or mixture

The product is classified as hazardous according to the Globally Harmonized System (GHS)

GHS Classification(s)	Toxic to Reproduction: Category 2 Acute Toxicity: Oral: Category 4 Acute Toxicity: Dermal: Category 4 Acute Toxicity: Inhalation: Category 4
------------------------------	---

Label elements

Signal word	WARNING
--------------------	----------------

Hazard pictograms



GHS07



GHS08

Hazard Statement(s)

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H360	May damage fertility or the unborn child.

Precautionary Statement(s):

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response statement(s):

P305 + P351 + P338.	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P352	IF ON SKIN: Wash with plenty of water.
P308 + P313.	IF exposed or concerned: Get medical advice/ attention
P330	Rinse mouth.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Storage Statement(s): Store Locked Up

Disposal Statement(s): Dispose of contents/container in accordance with relevant regulations.

Other Hazards No information provided

Additional information:

Hydrogen fluoride, a possible decomposition product, is extremely corrosive and a poison by all routes of entry. Hydrogen fluoride can penetrate the skin and produce burns, which may not be immediately painful or visible; the burns impact the lower layers of skin and bone tissue. Hydrogen fluoride exposures involving 20 percent of the body or more can be fatal through systemic fluoride poisoning. % of the mixture consists of component(s) of unknown acute inhalation toxicity. The reproductive toxicity associated with this product is expected to occur via the ingestion route only.

Other hazards which do not result in GHS classification:

Heat rays (infrared radiation) from flame or hot metal can injure eyes. Overexposure to brazing fumes and gases can be hazardous. Read and understand the manufacturer's instructions, Safety Data Sheets and the precautionary labels before using this product.

3 Composition/information on ingredients**Chemical characterization: Mixtures**

Description: Mixture: consisting of the following components.

Sustances/Mixtures			
CAS	HSR	Ingredient	Proportion
12712-38-8	1291	Potassium Borate	>50%
7789-23-3	7242	Potassium fluotitanate	20-40%
10043-35-3	2995	Boric Acid	20-40%
		Water	Remaining

Additional information:

For the listed ingredient(s), the identity and exact percentage(s) are being withheld as a trade secret.

Composition comments:

The term "Dangerous Components" should be interpreted as a term defined in Hazard Communication standards and does not necessarily imply the existence of a hazard. The product may contain additional nonhazardous ingredients or may form additional compounds under the condition of use. Refer to Sections 2 and 8 for more information.

4 First-aid measures

Description of first aid measures

General information: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Inhalation:

Remove person from contaminated area to fresh air. Apply artificial respiration if needed. Call a physician if symptoms develop or persist.

Skin contact:

Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. A 2.5 pct calcium gluconate gel applied topically after skin has been thoroughly washed will help reduce severity of symptoms. Get medical attention if irritation develops and persists.

Eye contact:

Immediately rinse eyes with water. Remove any contact lenses, and continue flushing eyes with running water for at least 15 minutes. Hold eyelids apart to ensure rinsing of the entire surface of the eye and lids with water.

Get immediate medical attention.**Ingestion:**

For advice, contact the National Poisons Centre: 0 800 764 766 or a doctor (at once). Do NOT induce vomiting. Immediately rinse mouth and drink a cupful of water. Never give anything by mouth to an unconscious person. Get medical attention immediately. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Information for doctor: Treat Symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Most important symptoms and effects, both acute and delayed

Contact with this material may cause burns to the eyes. Symptoms include itching, burning, redness, and tearing of eyes. Prolonged or repeated contact with the product may cause irritation of skin. Itching, redness, burning of skin. Edema. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Danger

Brazing hazards are complex and may include physical and health hazards such as but not limited to infrared radiation from flame or hot metal, physical strains, thermal burns due to hot metal or spatter and potential health effects of overexposure to brazing fume or dust. Refer to Section 11 for more information.

5 Fire-fighting measures

Extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

During fire, hazardous combustion products are released that may include: Hydrogen fluoride, fluorine-, boron- and potassium-containing compounds.

Advice for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Firefighting Equipment/instructions: Move containers from fire area if you can do so without risk.

Specific methods: Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards: No unusual fire or explosion hazards noted.

Additional information

Read and understand the Work Safe Australia and New Zealand Code of Practice on Welding Processes and “Standard for Fire Prevention During Welding, Cutting and Other Hot Work” before using this product. Section 274 of the Work Health and Safety Act (the WHS Act.)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Avoid inhalation of dust from the spilled material. Wear protective clothing as described in Section 8 of this SDS. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Methods and material for containment and cleaning up:

This product is miscible in water. Dike far ahead of spill for later disposal. Consider igniting spill or leak to eliminate toxic gas concerns. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Collect dust using a vacuum cleaner equipped with HEPA filter. Should not be released into the environment. Prevent product from entering drains. Do not allow material to contaminate ground water system.

Large Spills: Sweep up and place into a proper container for disposal. Avoid the generation of dusts during clean-up.

Small Spills: Wipe up spilled material and place in a suitable container for disposal.

Never return spills in original containers for re-use. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. This material and its container must be disposed of as hazardous waste. For waste disposal, see Section 13 of the SDS.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment (See Section 8). Wash thoroughly after handling. Avoid release to the environment. Read and understand the manufacturer's instruction and the precautionary label on the product.

Conditions for safe storage, including any incompatibilities**Storage:**

Store locked up. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS). Store in tightly closed original container in a dry, cool and well-ventilated place. Do not store in container made of glass or silicate-based material.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters**Exposure Guidelines:**

Follow standard monitoring procedures. No exposure standards allocated.

Refer to the Safe Environments risk management document – Welding Fume -

<http://www.safeenvironments.com.au/welding-fume/> The exposure standard refers to the publication by Work Safe Australia “Workplace Exposure Standard for Airborne Contaminants” with the Date of Effect being 22 December 2011. Work Safe Australia note that “exposure standards do not represent a fine dividing line between a healthy and unhealthy work environment. Natural biological variation and the range of individual susceptibilities mean that a small number of people might experience adverse health effects below the exposure standard.

Exposure Standards					
CAS	Ingredient	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³
1303-96-4	Sodium Borate Inhalation Fraction		2.5		6
16919-27-0	Potassium fluotitanate		2.5		
10043-35-3	Boric Acid				

Refer to Worksafe Australia for standards:

http://www.safeworkaustralia.gov.au/sites/SWA/about/Publications/Documents/639/Workplace_Exposure_Standards_for_Airborne_Contaminants.pdf

Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Do not eat, drink or smoke when using the product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Determine the composition and quantity of fumes and gases to which workers are exposed by taking an air sample from inside the welder's helmet if worn or in the worker's breathing zone. Improve ventilation if exposures are not below limits. Personal air monitoring is generally undertaken over a representative period of time undertaken to Australian Standard AS 3640-2009 Workplace atmospheres – Method for sampling and gravimetric determination of inhalable dust using IOM sampling heads with flow rate of 2.0 L/min. Keep away from foodstuffs, beverages and feed.

Engineering controls: No further relevant information available.

Ventilation

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of dust. Shower, hand and eye washing facilities near the workplace are recommended.

Breathing equipment:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a respirator when local exhaust or ventilation is not adequate to keep exposures below the TLV. In a confined space a supplied respirator may be required.

Protection of hands:

Wear protective gloves (i.e. latex, nitrile, neoprene).

Eye protection:

Wear safety glasses with side shields (or goggles).

Body protection: Chemical resistant clothing is recommended.



9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:	White/Blue
Colour:	White/Blue
Odour:	Odourless
Odour Threshold:	Not Available
pH-value:	8

Change in condition

Melting point/Melting range:	550-800
Boiling point/Boiling range:	550-800

Flash point:	Not Available
Evaporation rate:	Not Available
Flammability (solid, gaseous):	Not flammable

Explosion Properties:	Not Explosive
Oxidizing Properties:	Not Oxidizing

Vapour Pressure:	Not Available
Relative Density:	Not Available
Relative Density Temperature:	1.5 – 1.7
Specific Gravity:	Not Available
Vapour Density:	Not Available
Auto-Ignition:	Not Available
Decomposition Temp:	Not Available

Solubility in/Miscibility with water:	Soluble
Partition coefficient (n-octanol/water):	Not Available
Viscosity:	
Other Information:	No further relevant information available

10 Stability and reactivity

Reactivity: Carefully review all information provided in sections 10 below

Chemical stability: Stable under normal temperatures and pressures and conditions of storage.

Possibility of hazardous reactions: No dangerous reaction known under conditions of normal use.

Conditions to avoid: Contact with incompatible materials.

Incompatible materials: Strong oxidizing agents. Strong acids. Halogenated compounds. Silicate-based materials.

Hazardous decomposition products: Hydrogen fluoride, fluorine-, boron- and potassium-containing compounds.

Brazing fumes and gases cannot be classified simply. The composition and products: quantity of both are dependent upon the metal being joined, the process, procedure and filler metals and flux used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal being joined (such as paint, plating, or galvanizing), the number of operators and the volume of the worker area, the quality and amount of ventilation, the position of the operator's head with respect to the fume and fumes from chemical fluxes used in some brazing operations. When the wire or rod is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 3, plus those from the base metal and coating, etc., as noted above.

11 Toxicological information

Toxicity				
CAS	Ingredient	Oral Toxicity LD50	Intravenous Toxicity LD50	Inhalation Toxicity LD50
7440-42-8	Boron	>200mg/kg (rat)		
1303-96-4	Sodium Borate	3500-4100 mg/kg (rat)		

Information on toxicological effects:

Acute toxicity:

Toxic if swallowed

Skin Contact:

Prolonged or repeated contact may dry skin and cause irritation. Harmful in contact with skin. Hydrogen fluoride, a possible decomposition product, is extremely corrosive and a poison by all routes of entry. Hydrogen fluoride can penetrate the skin and produce burns, which may not be immediately painful or visible; the burns impact the lower layers of skin and bone tissue. Hydrogen fluoride exposures involving 20 percent of the body or more can be fatal through systemic fluoride poisoning.

Eye Contact:

May cause eye burns. Risk of serious damage to eyes.

Ingestion:

Harmful if swallowed. Ingestion may produce burns to the lips, oral cavity, upper airway, oesophagus and possibly the digestive tract.

Inhalation:

Harmful by inhalation. Dust may irritate respiratory system.

Respiratory or skin sensitization:

Knowledge about sensitization hazard is incomplete.

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Knowledge about sensitization hazard is incomplete.

Mutagenicity:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity:

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive:

Suspected of damaging the unborn child by ingestion. Possible reproductive hazard. Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility and sterility by repeated ingestion.

STOT – single exposure:

Not classified.

STOT – repeated exposure:

Knowledge about health hazard is incomplete.

Chronic effects: Prolonged exposure may cause chronic effects. May cause damage to the kidneys. Exposure to extremely high levels of fluorides can cause abdominal pain, diarrhea, muscular weakness, and convulsions. In extreme cases it can cause loss of consciousness and death. Prolonged overexposure to fluorides may increase fluoride content of bones and teeth, and may result in fluorosis, with mottling of teeth (in children) and brittleness of bones.

Further Information: Symptoms may be delayed.

12 Ecological information**Ecotoxicity:**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. Large amounts of the product may affect the acidity (pH-factor) in water with possible risk of harmful effects to aquatic organisms.

Persistence and Degradability: No data is available on the degradability of this product

Bioaccumulative Potential: No data is available on the degradability of this product

Mobility in soil: No data is available on the degradability of this product

Other adverse effects: No data is available on the degradability of this product

13 Disposal considerations**Waste treatment methods****Disposal Instructions:**

This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all applicable regulations.

Hazardous waste code: D002: Waste Corrosive material [pH <=2 or >=12.5, or corrosive to steel]

Uncleaned packagings:

Recommendation: Empty containers should be taken to an approved waste handling site for recycling or disposal.

14 Transport Information



	LAND TRANSPORT ADG	SEA TRANSPORT IMDG/IMO	AIR TRANSPORT IATA/ICAO
UN-Number ADG, IMDG/IMO, IATA/ICAO	3287	3287	3287
UN proper shipping name ADG, IMDG/IMO, IATA/ICAO	TOXIC LIQUID, CORROSIVE, INORGANIC, N.O.S.	TOXIC LIQUID, CORROSIVE, INORGANIC, N.O.S.	TOXIC LIQUID, CORROSIVE, INORGANIC, N.O.S.
Transport hazard class(es) ADG, IMDG/IMO, IATA/ICAO	6.1	6.1	6.1
Packing group ADG, IMDG/IMO, IATA/ICAO	III	III	III
Environmental hazards: Marine pollutant:	No information provided		
Special precautions for user			
Additional Information			
Hazchem code.			
GTEPG			
EMS			

15 Regulatory information

Product Name: WELDbraze® F55 Silver Brazing Flux Powder

Safety, health and environmental regulations/legislation specific for the substance or mixture:

Refer to the Australian Inventory of Chemical Substances – AICS at <https://www.nicnas.gov.au/chemicals-on-AICS#main>

Poison Schedule:

Classified as a Schedule 6 (S6) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
<https://www.legislation.gov.au/Details/F2016L01638>

Classifications:

Safework Australia and Worksafe New Zealand criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

Refer to the New Zealand Inventory of Chemical Substances at <https://www.hazardoussubstances.govt.nz/calculator>

Poison schedule: Classified as a Schedule 6 (S6) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). <https://legislation.govt.nz/bill/government/2006/0103/latest/DLM1048069.html>

Classifications: Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

16 Other information

References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice

Environmental Protection Authority of New Zealand

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Modell Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants, Safe work, Australia

American Conference of Industrial Hygienists (ACGIH)

Globally Harmonised System of classification and labelling of chemicals.

WELDING (1): Due to the diversity of welding techniques, processes, materials used, nature of the surface being welded and the presence of contaminants, the fumes & gases associated with welding will vary in composition and quantity. When assessing a welding process, the toxic fumes generated may not only be associated with the parent metal, filler wire or electrode. The welding/cutting arc may generate nitrogen oxides, carbon monoxide & other gases, whilst UV radiation emitted from some arcs generates ozone. Ozone may irritate mucous membranes and cause pulmonary oedema & haemorrhage. Shielding gases (e.g. carbon dioxide and inert gases i.e. argon and helium) in high concentrations, in confined spaces, may reduce oxygen in the atmosphere to dangerous levels, resulting in possible asphyxiation.

WELDING (2): In addition to complying with individual exposure standards for specific contaminants, where current manual welding processes are used, the fume concentration inside the welder's helmet should not exceed 5 mg/m³ (unless otherwise classified) when collected in accordance with Australian Standard AS 3853.1: Fume from welding and allied processes - Guide to methods for the sampling and analysis of particulate matter and AS 3853.2: Fume from welding and allied processes - Guide to methods for the sampling and analysis of gases. Airway irritation and metal fume fever are the most common acute effects from welding fumes. Reported to cause reduced sperm quality in welders.

WELDING (3): Other gases and fumes associated with welding processes include: Inert shielding gases (e.g. argon, carbon dioxide, helium) which may reduce the atmospheric oxygen content in poorly ventilated areas. UV-radiation and Infra-Red radiation may decompose chlorinated degreasing agents to form highly toxic and irritating phosgene gas. This may occur if a metal has been degreased but inadequately dried or when vapours from a nearby degreasing bath enter the welding zone.

WELDING (4): Welding fumes may contain a wide variety of chemical contaminants, including oxides and salts of metals and other compounds which may be generated from electrodes, filler wire, flux materials and from the welded material (e.g. painted surfaces). Welding stainless-steel and its alloys generates nickel and

chromium (VI) compounds. Welding fumes are retained in the lungs. Sparingly soluble compounds may be released slowly from the lungs. Welding fume is classified as possibly carcinogenic to humans (IARC Group 2B).

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Disclaimer:

We urge each end user and recipient of this SDS to study it carefully. If necessary, consult an industrial hygienist or other expert to understand this information and safeguard the environment and protect workers from potential hazards associated with the handling or use of this product.

GWS cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for use, handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

WARNING: PRODUCT COMPONENTS PRESENT HEALTH AND SAFETY HAZARDS. READ AND UNDERSTAND THIS SAFETY DATA SHEET (SDS). ALSO, FOLLOW YOUR EMPLOYER'S SAFETY PRACTICES.

The information contained herein relates only to the specific product. If the product is combined with other materials, all component properties must be considered. **BE SURE TO CONSULT THE LATEST VERSION OF THE SDS. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE FROM** Global Welding Supplies Ltd (GWS), 13 Patiki Road, Avondale, Auckland NZ 1026, Phone: +64 9 828 9888 Email: sales@gwsnz.co.nz and downloadable via www.globalweldingsupplies.co.nz website, **STATEMENT OF LIABILITY-DISCLAIMER**

To the best of the GWS knowledge, the information and recommendations contained in this publication are reliable and accurate as of the date prepared. However, accuracy, suitability, or completeness are not guaranteed, and no warranty, guarantee, or representation, expressed or implied, is made by GWS as to the absolute correctness or sufficiency of any representation contained in this and other publications; GWS assumes no responsibility in connection therewith; nor can it be assumed that all acceptable safety measures are contained in this and other publications, or that other or additional measures may not be required under particular or exceptional conditions or circumstances. Data may be changed from time to time.

[End of SDS]