Steadymig 265 Part No. 291129



"A Serious Tool for Serious Work"

The Steadymig 265 is a compact MIG/MAG unit with an operating range of 30 to 280 amps. As a compact unit, it combines power source, wire feed unit and control system in one cabinet and is suitable for use with gas or no-gas MIG welding. The unit is completed with a MIG gun, earth lead, regulator, wheels and bottle rack. The Steadymig 265 is the ideal unit for small to medium-sized businesses, home workshops, orchards and farms due to the input voltage being 230 volt single phase.

The machine offers superb welding characteristics, with the choice of eight voltage adjustments. This makes it suitable for welding with most gas shielded welding wires and small diameter flux cored wires.

The unit is fitted with a spot timer, for MIG spot welding. The machine is equipped with a very powerful fourwheel wire drive assembly. The feed mechanism features four driven rollers, capable of smooth and consistent feeding of 0.6 to 1.2mm diameter wires, through a 300 amp MIG gun. The Steadymig 265 is extremely mobile, and by fitting a suitable input power plug, a spool of wire and a bottle of shielding gas, the machine is ready for action.

- Simple operation
- Extremely mobile
- Robust
- 230 Volt Primary Input
- Fan Cooled
- 30 280 Amp Current Range

Primary Volts Primary Draw Recommended Fuse Current Range Voltage Steps Open Circuit Voltage Range Duty Cycle @ 30% Duty Cycle @ 60% Duty Cycle @ 100% Wire Sizes Drive System Weight Dimensions L x W x H Warranty 230 Volt Single Phase 44 Amps @ 30% Duty Cycle 40 Amp Slow Blow 30 – 280 Amps 8 18 - 46 Volts 250 Amps 26.5 Volts 180 Amps 23.0 Volts 140 Amps 21 Volts 0.6 – 1.2mm 4 Drive Roll 85 kg 830 x 500 x740mm 18 months



Simple, but sturdy, wire drive assembly. Solid aluminium components with drive rollers top and bottom.

Very powerful drive motor.



Comes complete with:

- Bottle Rack
- Spot Timer
- Earth Lead
- Argon Regulator
- 3.7m Mig Gun



CONSUMABLES

Description	2010
401 6 62 HD Nozzle 16 Bore 3 Rec	
403 22 30 0.8mm Surestart Con Tip	
403 22 35 0.9mm Surestart Con Tip	
403 22 1.0 1.0mm Surestart Con Tip	
403 22 364 1.2mm Surestart Con Tip	
403 22 52 1.3mm Surestart Con Tip	
404 20 Tough Lock Retaining Head	
154-14 Tough Lock Retaining Head	
415 35 15 0.9mm Std Liner 5 metre	
415 116 15 1.2 - 1.6mm Std Liner Re	d
Drive Rollers - refer to page 62	

old Per Pkt	Item No	Part No
2	231306	TREGNOZ401662
10	231363	TREGTIP4032230
10	231364	TREGTIP4032235
10	231365	TREGTIP4032210
10	231366	TREGTIP40322364
10	231367	TREGTIP4032252
2	231330	TREGHEAD40420
2	231123	TREGHEAD15414
1	231159	TREGLIN4153515
1 /	231162	TREGLIN41511615

Ph: 0800 699 353 sales@prolinewelding.com