Steadymig 402 with 4WD Feeder CV DC PHASE

Part No. 291151







Simple, Powerful, Reliable — What more could you need?

The Steadymig 402 and the Steadymig 4WD Feeder comes as a complete package with an operating range of 30 to 400 amps. The package includes 1 x Steadymig 402 Power Source, 1 x Steadymig 4WD Wire Feeder with a 4-wheel drive system, 5 metre extension leads between the feeder and the power source, and is completed with a MIG gun, earth lead, regulator, wheels, bottle rack and a feeder turntable.

The power source offers premium welding characteristics with the choice of 2 inductance tappings and 24 voltage adjustments (6 coarse and 4 fine) and is fitted with digital meters for easy reference of operating parameters. This makes it suitable for welding with most gas shielded and flux cored wires. The 4 wheel drive feeder is a simple but sturdy wire drive assembly, capable of feeding 0.6 to 1.6mm diameter wires through a 400 amp MIG Gun.

The Steadymig 402 with the Steadymig 4WD feeder is extremely mobile and by fitting a spool of wire and a bottle of shielding gas, the machine is ready for action.

- Simple operation
- **Extremely mobile**
- **Robust**

Warranty

- 400 Volt Primary Input
- **Fan Cooled**
- 30 400 Amp Current Range
- **Separate 4 Wheel Wire Feeder**

Primary Volts 400 Volt Three Phase **Primary Draw** 27 Amps @ 60% Duty Cycle Recommended Fuse 25 Amp Slow Blow Current Range 30 - 400 Amps Open Circuit Voltage Range 18 - 47 Volts 400 Amps 34 Volts Duty Cycle @ 60% 310 Amps 29.5 Volts Duty Cycle @ 100% Wire Speed 0 - 22 metres per minute Wire Sizes 0.6 - 1.6mm **Drive System** 4 Wheel Drive 156 kg 1000 x 555 x 810mm Dimensions L x W x H power source wire feeder 540 x 270 x 380mm



Simple, but sturdy, wire drive assembly. Solid aluminium components with drive rollers top and

18 months

Very powerful drive motor.



Comes complete with:

- **Bottle Rack**
- Spot Timer
- Earth Lead
- **Argon Regulator**
- 3.7m Mig Gun

CONSUMABLES

Description	Sold Per Pkt	Item No	Part No	
401 6 62 HD Nozzle 16 Bore 3 Rec	2	231306	TREGN0Z401662	
403 22 30 0.8mm Surestart Con Tip	10	231363	TREGTIP4032230	
403 22 35 0.9mm Surestart Con Tip	10	231364	TREGTIP4032230	
403 22 1.0 1.0mm Surestart Con Tip	10	231365	TREGTIP4032230	
403 22 364 1.2mm Surestart Con Tip	10	231366	TREGTIP4032230	
403 22 52 1.3mm Surestart Con Tip	10	231367	TREGTIP4032252	
404 20 Tough Lock Retaining Head	2	231330	TREGHEAD40420	
415 35 15 0.9mm Std Liner 5 metre		231159	TREGLIN4153515	
415 116 15 1.2-1.6mm Std Liner Rec	i	231162	TREGLIN41511615	

