



HOT WATER – OIL HEATED

Therm 1165-1

Tidy storage system
Practical stowing of the trigger gun with safety catch and lances

Integrated Hose drum
Practical design and features a longer length high-pressure hose complete with folding crank (Version incl. hose drum)

Digital operating panel
to control the water temperature and view cold/hot use operating time management

Removable covers
Protect the mechanical components from environmental factors and provide convenient access

Parking brake
For a secure stationary position

Cleaning Agent Intake
Injector system for dispensing of cleaning agents



Water output < 1000 l/h

Technical specifications		therm 1165-1	
		Three Phase	
Operating pressure adjustable	psi	2390	
Max. admissible overpressure	psi	2610	
Connected load	V / ~ / Hz / A	400 / 3 / 50 / 12	
Motor speed	Rpm	1400	
Water output	l/min l/h	19.4	1165
kW		5.5	
Volume water tank	l	4	
Hot water output adjustable	°C	12-82	
Steam level	°C	155	
Heating output	kW	78	
Fuel tank	l	35	
Power supply cable	m	7.5	
Dimensions L x W x H	mm	1050 / 800 / 1000	
Weight	kg	220	
Detergent Injector		●	
Equipment			
Hose drum		●	
Steel braided high-pressure hose	m	20	
Trigger gun with safety catch	Model	Starlet	
Stainless steel lance with flat jet nozzle	Nozzle size	● D2507	



TECHNICAL HIGHLIGHTS!

DIGITAL THERMOSTAT

The high-pressure cleaners of the therm-1-series are fitted with a digital thermostat which combines a variety of advantages in operation and service.

- Intelligent system analysis
- Reduction of fuel costs thanks to object-specific temperature specification
- Simple reading of the operating hours

