

SPECIFICATIONS

KEY FEATURES

INCLUDED

Cutter Capacity	50mm
epth of Cut	50mm
wist Drill Capacity	20mm
rill Chuck Capacity	13mm
Norse Taper	MT2
Countersink	30mm
apping	M20
lo Load Speed	100 - 500RPM
Notor Specification	1500W
lagnet Adhesion	13500N
ength	315mm
leight	586mm
Vidth	195mm
Nagnet Size	200 x 98mm
Veight	15KG
1 otor	110/230V
troke	140mm



CUTTER CAPACITY

50mm



DEPTH OF CUT
50mm



TWIST DRILL CAPACITY
20mm



COUNTERSINK

30mm



TAPPING M20



WEIGHT 15KG



MAGNET SIZE



MOTOR 1500W

- CARRY CASE
- INTERNAL COOLANT SYSTEM
- SAFETY STRAP
- STATIONARY RING
- 3mm HEXAGON KEY
- 6mm HEXAGON KEY
- ARBOR ASSEMBLY
- 13mm CHUCK
- DRILL CHUCK ADAPTOR
- DRILL CHUCK AND KEY
- DRIFT
- SAFETY GLASSES

PART CODE:

Element 50/1 (110V) Element 50/3 (230V)