

SPECIFICATIONS

KEY FEATURES

INCLUDED

50mm	Cutter Capacity
50mm	Depth of Cut
20mm	Twist Drill Capacity
13mm	Drill Chuck Capacity
MT2	Morse Taper
30mm	Countersink
M20	Tapping
100-500RPM	No Load Speed
1500W	Motor Specification
8430N	Magnet Adhesion
317mm	Length
640mm	Height
190mm	Width
277 x 190mm	Magnet Size
18KG	Weight
110/230V	Motor
150mm	Stroke



CUTTER CAPACITY
50mm



DEPTH OF CUT 50mm



TWIST DRILL CAPACITY



COUNTERSINK 30mm



TAPPING M20

20mm



WEIGHT



MAGNET SIZE



MOTOR 1500W

- CARRY CASE
- INTERNAL COOLANT SYSTEM
- SAFETY STRAP
- STATIONARY RING
- 3mm HEXAGON KEY
- 6mm HEXAGON KEY
- ARBOR SHANK
- ARBOR ASSEMBLY
- 13mm CHUCK
- DRILL CHUCK ADAPTOR
- DRILL CHUCK AND KEY
- DRIFT
- SAFETY GLASSES

PART CODE:

Element 50/1PM (110V) Element 50/3PM (230V)