

HW SERIES HOT WATER REELS

APPLICATION

Specially designed for hot water wash down applications in kitchens and food prep areas.

Perfect for use in food processing areas the vented case design allows the reel to be hygenically cleaned as required and allows for adequate air flow.

Available with or without a heavy duty, fully insulated washdown gun.

For accessories, guns and nozzles, see page 152.

HOSE TYPE	Nitrile blended PVC		
MEDIA	Hot water		
MINIMUM TEMP	-30°C		
MAXIMUM TEMP	85°C		
MAX PSI	225*		
FITTING TYPE	BSP**		
WEIGHT	12kg***		

Standard swivel configuration is brass; 316 stainless steel is available as an optional extra.

*Maximum working pressure of the hose is rated at 225psi @ 23°C, operating temperature 85°C @ 120psi.

**NPT, JIC, JIS and Metric threads are available on request.

***HW1015 weighs 11kg.



239mm

	HW SERIES							
	Model	Hose ID	Hose Length	Max PSI	Inlet Fitting	Outlet Fitting		
A O	HW1015	10mm	15m	240	3/8" BSPF	3/8" BSPM		
A P	HW1020	10mm	20m	240	3/8" BSPF	3/8" BSPM		
	HW1215	12mm	15m	240	1/2" BSPF	1/2" BSPM		
A C	HWG1015	10mm	15m	240	3/8" BSPF	Heavy Duty Washdown Gun		
A P	HWG1020	10mm	20m	240	3/8" BSPF	Heavy Duty Washdown Gun		
A P	HWG1215	12mm	15m	240	1/2" BSPF	Heavy Duty Washdown Gun		

 $\mathbf{A}^{(2)}_{\mathbf{A}}$ = Quick Ship Item, see inside back cover for more information.

Ph: 0800 699 353 sales@prolinewelding.com