



STRATA

SUPERIOR WELDING PRODUCTS

MIG ARC **200A**
EZIMIG215C




200A
Max Output (MIG)


10mm STEEL
Max Weld Thickness


15A
230V

200A Compact Inverter MIG/ARC Welder

- ✓ **MIG Inductance with adjustable pre-flow, post-flow, burnback & soft start settings** - greater control for MIG welding operation
- ✓ **Production tested with 440V** - Extreme stress testing in production for rugged reliability.
- ✓ **Professional 4-Roll Wire Feeder** - smooth & consistent wire feed
- ✓ **2T/4T/Spot Weld Trigger Control**
- ✓ **Dual digital display meters** - accurate pre-setting & feedback of parameters & output
- ✓ **IGBT Inverter Technology** - Smooth & stable output, increased reliability
- ✓ **Lightweight & compact design** - ideal for portable applications
- ✓ **Aluminium Chassis**
- ✓ **Industrial IP23 casing with front panel protection** - Resistant to damage, moisture & corrosion
- ✓ **Lift TIG operation** - for precise & aesthetically important jobs
- ✓ **Reverse polarity MIG welding operation** - suited for gas & gasless mig welding
- ✓ **High quality, over-specified components** - offers superior longevity & reliability
- ✓ **Intelligent protection system** - Temp., voltage & current sensors for increased reliability/safety
- ✓ **Generator Friendly** - Designed to work w/ generator power supply & protect from surges
- ✓ **Quick connect inlet gas fitting** - Tool-less easy connection of gas supply to machine



Description	Details
DIMENSIONS (LxWxH)	550 x 215 x 415mm
WEIGHT	20.5kg
INPUT POWER SUPPLY	230V AC 15A 50/60Hz
INPUT POWER SUPPLY TOLERANCE	+/- 10%
MAXIMUM INPUT CURRENT	42A
GENERATOR CAPACITY	10KVA
MIG CURRENT OUTPUT	40 - 200A
MIG OUTPUT VOLTAGE	16 - 24V
MIG DUTY CYCLE	200A@25% 155A@60% 120A@100%
WIRE FEEDING SPEED	1.5 - 16.5 m/minute
MMA CURRENT OUTPUT	10A - 160A
MMA O/C VOLTAGE	63V

Description	Details
MMA DUTY CYCLE	160A@15% 140A@60% 110A@100%
MIG DRIVE ROLLERS AVAILABLE	V Groove: 0.6 /0.8/0.9/1.0mm Knurled: 0.8/0.9/1.0mm U Groove: 0.8/1.0mm
MIG WIRE SPOOL SIZE	D200mm / D300mm 15KG
WELD THICKNESS	10mm Steel
INSULATION CLASS	IP23
MMA ROD SIZE	1.6 -5.0mm
POWER EFFICIENCY	85%
POWER FACTOR	0.65
STANDARDS	EN60974-1:2012
WARRANTY	48 Months

Includes:



EZIMIG215C
User guide, specs, videos

[LEARN MORE](#)



MIG Inverter Welder Accessories & consumables

○ Standard ● Optional ☆ Common Consumables

ACCESSORY:		EZIMIG215C
Arc Leads	○	AAL3550
Earth Leads	○	AEL3550
MIG Torch	○	MT250-4E
Argon Regulator	○	GR102ARFL
Gas Hose	○	GH08
MIG Starter Kit	●	MB25KIT
TIG Torch	●	17374
TIG Consumable Pack	●	DCKIT
Drive Roller 'V' Groove 0.6 - 0.8mm	○	17835 (x2)
Drive Roller 'V' Groove 0.9 - 1.0mm	○	17836 (x2)
Drive Roller 'V' Groove 1.0 - 1.2mm	●	17837 (x2)
Drive Roller 'U' Groove 0.8 - 1.0mm	●	17841 (x2)
Drive Roller 'U' Groove 1.0 - 1.2mm	-	-
Drive Roller 'U' Groove 1.2 - 1.6mm	●	17842 (x2)
Drive Roller Knurled 0.8 - 0.9mm	○	17838 (x2)
Drive Roller Knurled 1.0 - 1.2mm	●	17839 (x2)
Drive Roller Knurled 1.2 - 1.6mm	●	17840 (x2)
MIG Tips (MMT) 0.6 - 1.6mm	☆	0.6, 0.8, 0.9, 1.0, 1.2, 1.6mm
MIG Shrouds (MCN) 70 = Conical 71 = Cylindrical	☆	MTA2570 MTA2571
Tip Adaptors (MTA) 81 = M6 82 = M8	☆	MTA2581 MTA2582

Welding Magnets

WT-WMG03	3" Welding Magnet
WT-WMG05	5" Welding Magnet



Chipping Hammer

✓ Heavy duty chipping hammer for the trade

WT-SPCH	Spring Handle Chipping Hammer
---------	-------------------------------



Automatic Welding Helmets

- ✓ Variable Shade
- ✓ Complete with batteries ready to go
- ✓ Suitable for automotive DIY and industrial use.

WT180	Variable Shade 9-13
WT350	True Colour, 4 Sensor with grind function
SV3000	True Colour, Shade 5 - 13 + Grind Function (MIG/TIG/MMA/Plasma)
SV4000	Panoramic view with auto darkening side panels. Shade 4 - 13 + Grind Function (MIG/TIG/MMA/Plasma)
DW7000XL	True Colour, with grinding visor. Shade 5 - 13 + PRSL Filtration System (MIG/TIG/MMA/Plasma)




Mild Steel MIG Wire - ER70S-6

✓ Copper coated MIG wire for general purpose welding of mild steel using CO₂ or argon based shielding gases.

MW5KG06	5kg Spool - 0.6mm MIG wire (D200)
MW5KG08	5kg Spool - 0.8mm MIG wire (D200)
MW5KG09	5kg Spool - 0.9mm MIG wire (D200)



D300 MW15KG08S	15kg Spool - 0.8mm MIG wire (D300)
D300 MW15KG09S	15kg Spool - 0.9mm MIG wire (D300)
D300 MW15KG10	15kg Spool - 1.0mm MIG wire (D300)
D300 MW15KG12	15kg Spool - 1.2mm MIG wire (D300)



Industrial Storage Trolley

✓ Pull out drawer with storage, 25.85kg

32673	Integrated Trolley to suit Compact MIG Models
-------	---

