

**TECHNOLOGY PLASMA 60 XT 230V**



**NEW**

**Overview**

**TECHNOLOGY PLASMA 60 XT 230V**

cod. 816148

Inverter, compressed air plasma cutting system, with contact striking of pilot arc.

Allows a rapid, distortion-proof cutting, grid cutting and gauging of all conductive materials such as steel, stainless steel, galvanised steel, aluminium, copper, brass, etc.

**Features:**

- robust and impact resistant;
- reduced weight and dimensions;
- warning led for torch under voltage, protections;
- warning led for consumables change;
- torch automatic cooling;
- visualization of air pressure;
- thermostatic, overvoltage, undervoltage, overcurrent, air failure protections.

Complete with PH torch.



1 PH 230V



















CE MARKING



EAC CERTIFICATION

## Technical data

 <b>CODE</b>	CODE 816148	 <b>P<sub>MAX</sub></b>	MAX ABSORBED POWER 5,5 kW	 <b>MAX</b>	MAX CUTTING THICKNESS 20 mm
 <b>V<sub>1PH</sub></b>	SINGLE PHASE MAINS VOLTAGE 230 V		MAINS FUSE 20 A		COMPRESSED AIR CAPACITY 100 L/ min
 <b>F</b>	MAINS FREQUENCY 50 / 60 Hz	 <b>η</b>	EFFICIENCY 90 V		COMPRESSED AIR PRESSURE 4 - 5 bar
 <b>A<sub>MIN</sub> A<sub>MAX</sub></b> AC	CURRENT RANGE 10 - 60 A	 <b>φ</b>	POWER FACTOR (cosphi) 0,7	 <b>A<sub>MAX</sub></b> 40°C AC	MAX CURRENT (EN 60974-1) 50A @ 30 % A
 <b>IP</b>	PROTECTION DEGREE IP23	 <b>V<sub>0</sub> AC</b>	MAX NO LOAD VOLTAGE 313 V	 <b>W</b> <b>H</b> <b>L</b>	DIMENSIONS 50,6 x 18,2 x 29,2 cm
 <b>A<sub>MAX</sub></b>	MAX ABSORBED CURRENT 34 A				

Ph: 0800 699 353  
sales@prolinewelding.com