

The K 2000-Series



One-piece Roto-Mold chassis
Virtually indestructible

Total-stop system
Auto-shutdown feature improves seal life-span and reduces power consumption

Tidy storage system
Practical stowing of the trigger gun with safety catch and lances

Heavy Duty
Non-marking Wheels

Integrated Hose drum

Practical design and features a longer length high-pressure hose complete with folding crank (TST design)

Cleaning Agent Intake

Injector system for dispensing of cleaning agents

Pressure regulation

Fully adjustable control allows operating pressures to be set to suit any task



2 YEAR
COMMERCIAL
WARRANTY

Brass
Pump Head
10 YEAR
WARRANTY



| Technical specifications | | K2160TST single phase | |
|----------------------------------|----------------|--------------------------|-----|
| Operating pressure adjustable | psi | 2030 | |
| Max. admissible overpressure | psi | 2320 | |
| Connected load | V / ~ / Hz / A | 230 / 1 / 50 / 14 | |
| Motor speed | Rpm | 1400 | |
| Water output | l/min l/h | 11 | 660 |
| kW | | 3.3 | |
| Power supply cable | m | 5 | |
| Dimensions L x W x H | mm | 335 / 375 / 980 | |
| Weight | kg | 41 | |
| Detergent Injector | | ● | |
| Equipment | | | |
| Hose drum | | ● | |
| Steel braided high-pressure hose | m | 15 | |
| Trigger gun with safety catch | Model | M2000 | |
| Dirtkiller lance | Nozzle size | ● 042 | |
| Vario-Jet lance | Nozzle size | ● 042 | |

