











Total-stop system with

delayed motor cut-off Auto-shutdown feature improves seal lifespan and reduces power consumption

Pressure regulation

Fully adjustable control allows operating pressures to be set to suit any task



KN599TST

20

M2000

035 M20035

Integrated Hose drum

Practical design and features a longer length high-pressure hose complete with folding crank

Integrated water tank

Prevents damage to the high-pressure pump caused by a lack of water



Roto-Mold-Chassis Virtually indestructible

Cleaning Agent Intake

Injector system for dispensing of cleaning agents

Steel braided high-pressure hose Trigger gun with safety catch

Stainless steel lance with flat jet nozzle

Dirtkiller lance

			KQJJJIJI	
Technical specifications			Single	Phase
Operating pressure adjustable	psi		2175	
Max. admissible overpressure	psi		2390	
Connected load	V / ~ / F	łz/A	230 / 1 / 50 / 14	
Motor speed	Rpm		1400	
Water output	I/min	l/h	10	600
kW	·		3.2	
Volume water tank	I		10	
Power supply cable	m		5	
Dimensions L x W x H	mm		780 / 395 / 870	
Weight	kg		60	
Detergent Injector			•)
Equipment				THE RES
Hose drum			•)

Model

Nozzle size

Nozzle size









