



Total-stop system with delayed motor cut-off

Auto-shutdown feature improves seal lifespan and reduces power consumption

Pressure regulation

Fully adjustable control allows operating pressures to be set to suit any task

Cleaning Agent Intake

Injector system for dispensing of cleaning agents

Integrated Hose drum

Practical design and features a longer length high-pressure hose complete with folding crank

Integrated water tank

Prevents damage to the high-pressure pump caused by a lack of water

Roto-Mold-Chassis

Virtually indestructible



KQ799TST

Three Phase

Technical specifications		KQ799TST	
		Three Phase	
Operating pressure adjustable	psi	2610	
Max. admissible overpressure	psi	2900	
Connected load	V / ~ / Hz / A	400 / 3 / 50 / 8.5	
Motor speed	Rpm	1400	
Water output	l/min l/h	13	780
kW		3.5	
Volume water tank	l	10	
Power supply cable	m	7.5	
Dimensions L x W x H	mm	780 / 395 / 870	
Weight	kg	60	
Detergent Injector		●	
Equipment			
Hose drum		●	
Steel braided high-pressure hose	m	20	
Trigger gun with safety catch	Model	M2000	
Dirtkiller lance	Nozzle size	● 045	
Stainless steel lance with flat jet nozzle	Nozzle size	● M20045	

